



# LIFEBREATH® MAX SERIES

Indoor Air Systems **HEAT & ENERGY RECOVERY VENTILATORS**

Model	Dimensions H x W x D (in.)	Airflow CFM (L/s)			Apparent Sensible Effectiveness (ASE) @ 0°C (32°F)	Sensible Recovery Efficiency (SRE) @ 0°C (32°F)	ENERGY STAR Certified	Performance Highlights
		(50 PA)	(75 PA)	(100 PA)				
<b>155 MAX 2019*</b>	Recirculating Defrost 18.681 x 33.625 x 14.75	159 (75)	148 (70)	138 (65)	85% 64 CFM (30 L/s)	75% 64 CFM (30 L/s)		Door port balancing. Featuring the high efficiency HEX core. *2019 denotes Energy Star certification, not manufacture date.
<b>205 MAX</b>	Recirculating Defrost 18.75 x 33.625 x 15	193 (91)	182 (86)	170 (80)	85% 64 CFM (30 L/s)	76% 64 CFM (30 L/s)	NO	Top port design for flexible installations with door port balancing featuring the high efficiency HEX core.
<b>267 MAX</b>	Recirculating Defrost 18.75 x 33.625 x 15	271 (128)	267 (126)	261 (123)	84% 64 CFM (30 L/s)	75% 64 CFM (30 L/s)	NO	Highest airflow available in a single core EC Motor powered HRV. Offers maximum heat recovery and efficiency. Ideal for large custom homes and fully dedicated installations.
<b>267 MAX ERV</b> 	Recirculating Defrost 18.75 x 33.625 x 15	286 (135)	278 (131)	271 (128)	85% 64 CFM (30 L/s)	77% 64 CFM (30 L/s)	NO	<b>AUTO BALANCE</b> feature allows user specified airflows to be continuously monitored and balanced. High efficiency EC motor. Fault Indicating Display option available. Damper shuts off outdoor air supply.
<b>195 DCS</b>	Damper Defrost 18.75 x 49 x 14.75	210 (99)	193 (91)	176 (83)	91% 64 CFM (30 L/s)	80% 64 CFM (30 L/s)	NO	5 <sup>th</sup> port damper defrost. Double core system for maximum heat recovery and energy efficiency. Side ducted.
<b>MAX XTR</b> 	Fan Defrost 22 x 26 x 10	191 (90)	184 (87)	176 (83)	89% 64 CFM (30 L/s)	84% 64 CFM (30 L/s)	NO	<b>AUTO BALANCE</b> feature allows user specified airflows to be continuously monitored and balanced. Designed for high-rise condos, apartments and townhomes with limited mechanical space. Ceiling or wall mount. Flexible CFM operational range.



## INCLUDED ACCESSORIES



### DXPL03 | DIGITAL WALL CONTROL

- Intuitive Auto Balance feature<sup>1</sup>
- Five speed fan setting
- Standby setting (fan speed 0)
- Electronic dehumidistat
- 20/40/60 HIGH speed override button
- Compatible with Wireless Timer
- Easy to read back-lit LCD screen
- Slim-line design
- Connect to 3-wire 20 gauge low voltage wire
- Continuous motor speed adjustment to maintain user defined airflow (CFM)<sup>1</sup>
- Quick Balance: adjusting only speed 5 will cause all other speeds adjust automatically<sup>1</sup>
- All 5 speeds are adjustable<sup>1</sup>
- Auto Balance indicator shows when the unit is actively controlling motor speeds<sup>1</sup>
- Airflow is continuously measured with differential pressure readings<sup>1</sup>

<sup>1</sup> - denotes feature only available on Auto Balance and FID units.



### HANGING STRAPS | 99-80-102

- Included with most MAX SERIES products
- Easy mount system enables pre-assembly on floor
- Adjustable clip simplifies leveling